

DENASOL KT
p-toluenesulphonic acid

TECHNICAL PROPERTIES

| | |
|----------------------------|---------------------------------|
| Physical form | : Powder, crystal |
| Appearance | : Pink - Brown coloured crystal |
| PTSA | : 84,00 – 90,00 % |
| Free Sulphuric Acid | : Max. 5,00 % |
| Iron | : Max. 30 ppm |

GENERAL PROPERTIES

- It is used as a catalyst in esterification reactions.
- It is used as a hardener in urea - formaldehyde, melamine - formaldehyde and phenol - formaldehyde resins.

PACKAGING

30 kg PE bag.

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated area. The product must be stored in a dry place between + 5°C and + 25°C. Shelf life is 1 year under conditions of normal use.

HEALTH – SAFETY

Refer to safety data sheet for health and safety informations.

Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the product is beyond the control of Deteks Kimya Sanayi A.S., and no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from misuse of the product as such, or in combination with other materials.

İstanbul Deri Organize Sanayi Bölgesi
Ö-1 Parsel No:1 Aydınli Orhanlı Mevkii
Tuzla - İSTANBUL/TURKIYE
Tel :(+90216) 394 02 40
Fax:(+90216) 394 09 65
info@deteks.com.tr
www.deteks.com.tr

